



SPC FLOORING
stone polymer composite

2



SPC FLOORING
stone polymer composite





Aluminium p 4



Argon p 7



Beryllium p 8



Boron p 11



Calcium p 12



Lithium p 44



Magnesium p 47



Mnemea p 48



Neon p 51



Nitrogen p 52



Cale p 15



Calice p 16



Calisto p 19



Carbon p 20



Carme p 23



Oxygen p 55



Pandia p 56



Phosphorus p 59



Potassium p 60



Scandium p 63



Chlorine p 24



Erinome p 27



Eufeme p 28



Fluorine p 31



Harpalice p 32



Silicon p 64



Sodium p 67



Sulfur p 68



Tebe p 71



Temisto p 72



Helium p 35



Hydrogen p 36



Kallichore p 39



Kore p 40



Leda p 43



Titanium p 75



Vanadium p 76

CONTENTS



SPC FLOORING
stone polymer composite



SPC FLOORING
stone polymer composite

Hydrogen

size:
18 x 122 cm
7" x 48"





Argon

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Beryllium

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Boron

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Calcium

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Cale

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Calice

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Calisto

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Carbon

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Carme

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Chlorine

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Erinome

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Eufeme

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Fluorine

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Harpalice

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Helium

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Hydrogen

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Kallichore

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Kore

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Leda

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Lithium

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Magnesium

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Mnemea

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Neon

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Nitrogen

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Oxygen

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Pandia

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Phosphorus

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Potassium

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Scandium

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Silicon

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Sodium

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Sulfur

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Tebe

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Temisto

size:
18 x 122 cm
7" x 48"





SPC FLOORING
stone polymer composite

Titanium

size:
18 x 122 cm
7" x 48"



SPC FLOORING
stone polymer composite

Vanadium

size:
18 x 122 cm
7" x 48"



TECHNICAL DATA

Physical properties	Specification 0.3 mm	Specification 0.5 mm
Plank Length	1220 mm	1220 mm
Plank Width	180 mm	180 mm
Edge Profile	4 sides beveled	4 sides beveled
Finish	UV coating	UV coating
Wear layer	0.3mm/12mil	0.5mm/20mil
Recommended Usage	Residential and Commercial	Residential and Commercial
Installation Method	Glueless Floating	Glueless Floating

Technical properties	Specification 0.3 mm	Specification 0.5 mm
Total Thickness (ISO 23346:2006)	Pass	Pass
Dimensional Stability	≤0.15%	≤0.15%
Residual Indentation (ASTM F1914-07)	≤0.1%	≤0.1%
Behaviour to fire (EN13501-1) Bfl-S1	Bfl-S1	Bfl-S1
Slip Resistance	R10	R10
Castor Chair Suitability (EN425) Pass	Pass	Pass
VOC Emission (EN ISO 16000-06)	A+	A+
Phthalate Free (EN 14372:2004)	Pass	Pass
PCP Pentachlorophenol (DIN CEN/TS 14494:2003)	Pass	Pass
Recommended Usage	Class 23	Class 33
Use in Wet Areas	Yes	Yes
Underfloor Heating Suitability (EN1264-2)	Suitable, max 27°C/81°F	Suitable, max 27°C/81°F
Impact Resistance (EN13329)	Big Ball ≥1000mm	Big Ball ≥1000mm



Resilient



Waterproof



Durable



No Formaldehyde

PACKING

Size	Thickness (mm)	Kg / Pc (Kgs)	Pcs / Ctn	G.W / Ctn (Kgs)	Ctns / Plt	Plts / 20Gp	G.W / 20Gp (Kgs)	Sq.m / 20Gp	REMARK
7"x48" (inch) 180x1220 (mm)	4	19	10	39	70	20	26.500	3.075	1.5mm underlay

SPC FLOORING

stone polymer composite

IMPORTANT NOTICE

The reproduction of the colors is approximated. All Flooring by QUALITY ENGINEERING reserves the right to alter or amend the products here stated. Price codes and product codes should be checked.

CAUTION : READ BEFORE INSTALLATION

Disclaimer on tiles: SPC may have variations in color, shiny effect and smoothness. These variations are affected by light and brightness. No claims will be accepted due to these changes in surface appearance. Due to the delicate nature of these products, we do not recommend the application of strong cleaning products, solvents, polishing, or buffing to the tile. BEFORE INSTALLATION, we recommend the inspection of all tiles. No claims will be accepted after the tiles have been installed.



by

